

DATE	19.03.2014
DOC.NO	
PAGE NO	1
REV.NO	0
REV.DATE	

TECHNICAL DATA SHEET

Product : Polypropylene

Product Description : ENDLESS FILAMENTS MELTBLOWN, THERMALLY BONDED.
 Raw Material : 100 % PP
 Application on Fabric : MB/HYDROPHOBIC
 Treatment :
 Fabric Colour : WHITE
 Customer Name :
 Weight : **30 GSM**
 Width :
 Packing : PE BAG WITH LABEL

PROPERTIES	TEST METHOD	UNIT	TARGET
WEIGHT	NWSP 130.1.R0 (15)	gsm	30
THICKNESS	NWSP 120.1.R0 (15)	mm	0,44
TENSILE STRENGTH	NWSP 110.4.R0 (15)	N/5 cm	11,2
			9,6
ELONGATION AT BREAK	NWSP 110.4.R0 (15)	%	38,0
			56,6
ABSORPTION	NWSP 010.4.R0 (15)	%	1529,0

Tolerances For The Average Results

Weight	± 5 %	Roll Tolerance Length : - 0 / +5% against target / ordered length Width : Up to 150 cm in width = -0mm/+5mm Over 150 cm in width = - 0mm/+10 Splice : Maxium five splices per roll
Thickness	± 10 %	
Tensile Strenght	± 15 %	
Elongation	± 15 %	
Hydrostatic Head	± 15 %	
Liquid Strike-Through Time	± 0,5 %	
Air Permeability	± 20 %	
Absorption	± 20 %	

The product is wound onto cardboard cores and then wrapped in polyethylen film. Bar code labels with product code, description and lot details are applied to the outside of each pack and a small label is applied to each roll. Suitable sized rolls may be palletised and the pallet load cling-wrapped

Preperation Date	QUALITY CONTROL APPROVAL
07.02.2020	